

Wall & Slab Formwork - Hand-Set Solution

www.nova-tec.com.au

AluFix is the optimum light-weight, high-performance, hand-set wall and slab system - perfect when crane time is not available and working space is limited.

The all-plastic, 100% wood-free polypropylene facing will last as long as the sturdy aluminium frame and does away with plywood waste and refacing costs. AluFix panels deliver a smooth, clean, consistent and even concrete finish from the first pour to the last.

When labour costs are high and cost savings are required, AluFix creates an attractive cost-performance ratio, making it the perfect choice for the quality-conscious contractor.

Suitable for large and small residential and commercial projects.

Key features include:

- Permissible fresh concrete pressure of 55 kN/m²
- Three tying methods in one system
- Tie rod fixture - attaches to multi-function profile, no loose parts or accessories, saves assembly time
- Closed hollow aluminium profile - Robust, ergonomic grip profile, high-grade powder-coated finish, impact and scratch-resistant surface
- Multi-function profile with welded-in DW nut for simple attachment of all parts with the flange screw
- Intelligent design - Continuous aligned connection of panels using assembly lock with only a few hammer blows
- High-quality Alkus all-plastic facing.



Panel Heights (mm)	3000 / 1500
Panel Widths (mm)	750 / 600 / 500 / 450 / 400 / 300 / 250
Largest Panel (mm)	3000 x 750 with a weight of 49.70 kg
Tie Holes Per Panel Height	3 for 3000mm, 2 for 1500mm